## **PCT**


# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> :		(11) International Publication Number: WO 99/6243
A61F 2/16	A1	(43) International Publication Date: 9 December 1999 (09.12.9
(21) International Application Number: PCT/US (22) International Filing Date: 20 April 1999 (		BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, L
(30) Priority Data: 09/088,910 2 June 1998 (02.06.98)	1	Published  With international search report.
<ul> <li>(71) Applicant: ALCON LABORATORIES, INC. [US/U South Freeway, Fort Worth, TX 76134–2099 (US)</li> <li>(72) Inventors: BROWN, Kyle; 6505 Sheridan Road, For TX 76134 (US). VAN NOY, Stephen, J.; 4709 Ra Road, Fort Worth, TX 76109 (US).</li> <li>(74) Agents: SCHIRA, Jeffrey, S. et al.; Alcon Laboratoria &amp; D Legal Dept., Q-148, 6201 South Freeway, For TX 76134–2099 (US).</li> </ul>	). ort Wor inch Vi es, Inc.	h, w R

(54) Title: IMPROVED PLUNGER



#### (57) Abstract

An intraocular lens injector plunger having a blunt, rounded tip offset from the centerline of the plunger rod. The offset tip assures that the tip is biased downward against the bottom of the cartridge bore. Such a downward bias helps prevent the tip from riding up over the IOL and being folded within the IOL. The offset also helps prevent the haptics of the IOL from becoming trapped between the plunger rod and the cartridge bore, thereby damaging the haptics and/or preventing the IOL from being advanced down the bore.

## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑÜ	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	. TR	Turkey
ВG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	1E	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazi)	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of Americ
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

#### IMPROVED PLUNGER

This invention relates to intraocular lenses (IOLs) and more particularly to cartridges use to inject IOLs into an eye.

5

10

15

20

25

30

#### Background of the Invention

The human eye in its simplest terms functions to provide vision by transmitting and refracting light through a clear outer portion called the comea, and further focusing the image by way of the lens onto the retina at the back of the eye. The quality of the focused image depends on many factors including the size, shape and length of the eye, and the shape and transparency of the comea and lens.

When trauma, age or disease cause the lens to become less transparent, vision deteriorates because of the diminished light which can be transmitted to the retina. This deficiency in the lens of the eye is medically known as a cataract. The treatment for this condition is surgical removal of the lens and implantation of an artificial lens or IOL.

While early IOLs were made from hard plastic, such as polymethylmethacrylate (PMMA), soft, foldable IOLs made from silicone, soft acrylics and hydrogels have become increasingly popular because of the ability to fold or roll these soft lenses and insert them through a smaller incision. Several methods of rolling or folding the lenses are used. One popular method is an injector cartridge that folds the lenses and provides a relatively small diameter lumen through which the lens may be pushed into the eye, usually by a soft tip plunger. The most commonly used injector cartridge design is illustrated in U.S. Patent No. 4,681,102 (Bartell), and includes a split, longitudinally hinged cartridge. Similar designs are illustrated in U.S. Patent Nos. 5,494,484 and 5,499,987 (Feingold) and 5,616,148 and 5,620,450 (Eagles, et al.). In an attempt to avoid the claims of U.S. Patent No. 4,681,102, several solid cartridges have been investigated, see for example U.S. Patent No. 5,275,604 (Rheinish, et al.) and 5,653,715 (Reich, et al.).

These prior art devices used plungers that were substantially symmetrical about a longitudinal axis and generally contained a cylindrical or flared soft tip that completely filled the bore of the injector cartridge. See, for example, U.S. Patent Nos. 4,681,102 (Bartell) and 4,919,130 (Stoy, et al.), and WIPO Publication No. WO 96/29956, the entire contents of which are incorporated herein by reference. Other plungers had hooked or

5

10

15

20

25

30

forked tips meant to grasp the edge of the IOL. See for example, U.S. Patent Nos. 4,573,998 (Mazzocco), 5,494,484 and 5,499,484 (Feingold), 5,616,148 and 5,620,450 (Eagles, et al.) and 5,653,715 (Reich, et al.), the entire contents of which are incorporated herein by reference. One plunger tip recently commercially introduced is designed so that the IOL rolls around the tip as the IOL is advanced down the cartridge. See U.S. Patent No. 5,735,858 (Makker, et al.), the entire contents of which is incorporated herein by reference.

While these symmetric plunger tip designs work well with robust, rubbery, elastic lens materials, the performance of these tip designs is less than optimal when used with a viscoelastic material, such as a soft acrylic. In particular, the tip design that encourages the IOL to roll around the tip as the tip is advanced down the cartridge bore significantly increases the chances of damage to soft acrylic IOLs. The inventors have also discovered that viscoelastic IOL materials tend to flow around the plunger tip, regardless of tip design, and prior art tips de not address this material property adequately. Accordingly, a need continues to exist for an IOL injector plunger designed to optimize performance when used with a viscoelastic material.

#### Brief Summary of the Invention

The present invention improves upon prior art lens injector plungers by providing a plunger having blunt, rounded tip offset from the centerline of the plunger rod. The offset tip assures that the tip is biased downward against the bottom of the cartridge bore. Such a downward bias helps prevent the tip from riding up over the IOL and being folded within the IOL, as is illustrated in FIGS. 5 and 6 of U.S. Patent No. 5,735,858. Folding the IOL about the plunger tip may result in tip advance without advancing the IOL, particularly with viscoelastic materials which tend to be more adherent than elastic or rubber materials. The offset also helps prevent the haptics of the IOL from becoming trapped between the plunger rod and the cartridge bore, thereby damaging the haptics and/or preventing the IOL from being advanced down the bore.

It is accordingly an object of the present invention to provide a lens injector plunger having a rounded tip.

It is a further object of the present invention to provide a lens injector plunger

3

having an offset tip.

5

10

15

20

25

30

It is a further object of the present invention to provide a lens injector plunger that minimizes the potential for damage to the optic and/or the haptics.

Other objects, features and advantages of the present invention will become apparent with reference to the drawings, and the following description of the drawings and claims.

#### Brief Description of the Drawings

FIG. 1 is a partial side elevational view of the lens injector plunger of the present invention.

FIG. 2 is a top plan view of the lens injector plunger of the present invention.

FIG. 3 a front elevational view of the lens injector plunger of the present invention.

FIGS. 4-4C are partial cross-sectional views of the intraocular lens injector plunger of the present invention traveling down the bore of the lens injector cartridge and handpiece.

### Detailed Description of the Invention

As best seen in FIG. 4, intraocular lens injectors suitable for use with the present invention generally consist of handpiece 10, cartridge 12 and plunger 14. Cartridge 14 contains bore 16 through which the intraocular lens (not shown) is pushed by plunger 14 until the lens exist bore 16 at nozzle 18. Cartridge 10 and handpiece 12 may be of any suitable design well-known in the art.

As best seen in FIGS. 1-3 plunger 14 contains tip 20 that contains IOL contacting portion 22 that is off set asymmetrically relative to longitudinal centerline 24. Portion 22 also contains convexly rounded nose 26. Length A of portion 22 preferably is between 0.10 inches and 0.20 inches, with 0.127 inches being preferred. Width D of portion 22 preferably is between 0.060 inches and 0.100 inches, with 0.083 inches being most preferred. The radius R of nose 26 may be any suitable dimension, with between 0.030 inches and 0.050 inches being preferred and 0.042 inches being most preferred.

The offset distance C from centerline 24 will vary depending upon the diameter of

bore 16 and plunger rod 15 and the thickness B of portion 22. By way of example, when bore 16 has a diameter of around 0.100 inches, plunger rod 15 has a diameter G of around 0.060 inches and thickness B of portion 22 is between 0.030 inches and 0.060, offset C generally will be between 0.047 inches and 0.077 inches.

In use, as seen in FIGS. 4-4C, as plunger 14 travels down bore 16, offset portion 22 of tip 20 maintains constant contact with and pressure against bore wall 28, because rod 15 must be deflected slightly in order for tip 20 to enter bore 16. To facilitate the entry of tip 20 into bore 16, cartridge 10 may contain ramped or flared opening 30 so that the initial contact between cartridge 12 and portion 22 occurs on flared portion 30.

5


10

While certain embodiments of the present invention have been described above, these descriptions are given for purposes of illustration and explanation. Variations, changes, modifications and departures from the systems and methods disclosed above may be adopted without departure from the scope or spirit of the present invention.


I claim:

1. An intraocular lens injection system, comprising:

- a) a handpiece having a plunger;
- b) an injection cartridge having a bore with a longitudinal centerline, the
- cartridge adapter to be received in the handpiece so that the plunger can travel
- down the bore;
- 6 c) a tip on the plunger, the tip having a rounded nose and a lens contacting
- portion that is offset asymmetrically relative to the centerline of the bore.
- The lens injector system of claim 1 wherein the rounded nose has a radius of between 0.030 inches and 0.050 inches.
- 3. A plunger for use with an intraocular lens injection system, comprising:
- a) a plunger rod;
- b) a tip on the plunger rod, the tip having a rounded nose and a lens contacting
- 4 portion that is offset asymmetrically relative to the centerline of the bore.
- The plunger of claim 3 wherein the rounded nose has a radius of between
- 2 0.030 inches and 0.050 inches.



SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)

# INTERNATIONAL SEARCH REPORT

PCT/US 99/08660

	FICATION OF SUBJECT MATTER					
IPC 6	A61F2/16					
According to	International Patent Classification (IPC) or to both national classifica	ation and IPC				
<u>-</u> _	SEARCHED					
	currentation searched (classification system followed by classification	n symbols)				
IPC 6	A61F					
Documentat	ion searched other than minimum documentation to the extent that su	uch documents are included in the fields se	arcned			
Flectronic d	ata base consulted during the international search (name of data bas	and where practical search terms (read)	<del></del>			
		•				
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT					
Category °	Citation of document, with indication, where appropriate, of the rele	evant passages	Relevant to claim No.			
Y	WO 97 15253 A (STAAR SURGICAL CO	INC)	1,3			
	1 May 1997 (1997-05-01)		´ ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '			
	page 21, line 15; figure 10					
v		01.0	, ,			
Y	WO 96 28122 A (WOLF JOHN R ;FEING VLADIMIR (US))	OLU	1,3			
	19 September 1996 (1996-09-19)					
	page 13, line 1 - line 14; figur	es 34,35				
		,				
Α	US 4 934 363 A (SMITH GREGORY M	ET AL)	1,3			
	19 June 1990 (1990-06-19)	4				
	column 4, line 36 - line 49; fig	jure 4				
			-			
			į			
			j			
			-			
Furti	ner documents are listed in the continuation of box C.	Y Patent family members are listed i	n annex.			
° Special ca	tegories of cited documents :	T" later document published after the inter	national filing date			
"A" document defining the general state of the art which is not or priority date and not in conflict with the application but						
considered to be of particular relevance invention  "E" earlier document but published on or after the international "Y" document of particular relevance; the claimed invention						
"X" document of particular relevance; the claimed invention filling date cannot be considered novel or cannot be considered to "L" document which may throw doubts on pnority claim(s) or involve an inventive step when the document is taken alone						
which is cited to establish the publication date of another "Y" document of particular relevance; the claimed invention						
"O" docume	"O" document referring to an oral disclosure, use, exhibition or document is combined with one or more other such docu-					
"P" docume	neans ont published prior to the international filing date but	ments, such combination being obviou in the art.				
later th	nan the priority date claimed	"&" document member of the same patent f	amily			
Date of the	actual completion of the international search	Date of mailing of the international sea	rch report			
1	0 August 1999	18/08/1999				
1	v nagast 1777	10/00/1333				
Name and r	nailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2	Authorized officer				
	NL - 2280 HV Rijswijk					
	Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Kanal, P				

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Ir stional Application No PCT/US 99/08660

Patent document cited in search report		Publication date	Patent family member(s)		Publication date	
WO 9715253	A	01-05-1997	US	5616148 A	01-04-1997	
			US	5772666 A	30-06-1998	
			AU	7476996 A	15-05-1997	
			CA	2234002 A	01-05-1997	
			CN	1200659 A	02-12-1998	
			EP	0858304 A	19-08-1998	
			ÜS	5860984 A	19-01-1999	
WO 9628122	A	19-09-1996	AU	5309896 A	02-10-1996	
	• •		CA	2215182 A	19-09-1996	
			CN	1185100 A	17-06-1998	
			US	5772666 A	30-06-1998	
			US	5860984 A	19-01-1999	
			US	5800442 A	01-09-1998	
US 4934363	<u>-</u>	19-06-1990	NONE			